

# L43H7B

## 43" All-In-One Digital Kiosk with BrightSign® built-in



### Reliable All-In-One Commercial LCD LED Digital Poster Solution

Engaging audiences has never been easier. Introducing the new L43H7B all-in-one free-standing digital kiosk solution with BrightSign built-in. These highly reliable displays offer a cost-effective solution ideal for retail, hospitals, public spaces, government, and more. Our robust full HD screens are powered by BrightSign, the industry leader in digital signage media players and software. The integrated solid-state BrightSign HD222 player delivers flawless Full HD 1080p60 single video decoding, HTML support, networked content playback as well as an abundant set of features like Interactivity via the GPIO port, remote snapshot, live text and media feeds and multi-zone. Create effortless presentations with BrightSign's free BrightAuthor software.



### IP Streaming

HD Video IP streaming available on all BrightSign built-in displays. Buffer media streams for smooth playback. Play streaming media in HTML5 assets or in BrightAuthor's video, audio or MJPEG stream states.



### Industrial Ultra Slim Design

A sleek, stylish design that offers the ruggedness needed in today's market place and the simple installation and maintenance design wanted by today's technicians.



### UDP Controls

Supported via the Ethernet port for video wall synchronization, mobile device interactivity and messaging between BrightSign and third-part devices such as projectors, lighting, etc. and integrate with other show controllers.

Model	L43H7B
Display Screen Size	43"
Resolution	1920 x 1080p
Product Size (inches)	26.38" (W) x 70.35" (H) x 15.75" (D)
Display Size (inches)	20.82" (W) x 37.05" (H)
Net Weight	121.25 lbs
Brightness	450 cd/m <sup>2</sup>
Aspect Ratio	9:16
Contrast Ratio	1100:1
Input Power Voltage	AC 110-240 V (50Hz-60Hz)
Working Temperature	32° to 122° F
Sound	6W, 8Ω
Colors	16.7M
Color Temp	10,000K
Viewing Angle	178°
Integrated Player	BrightSign HD222
Software	BrightAuthor by BrightSign
Control	GPIO
SD Slot	SDHC and SDXC
LAN	RJ45 (12/100)
Audio Out	3.5mm Stereo Mini Jack
USB	2.0 high speed x(2)
Panel Life	30,000 hours
Accessories	Remote control, AC Power Cord, CD, Key, User Manual

## Help Boost Your Sales Using Digital Signage!