## UV470PD









## **Outdoor Skirted Kiosk**

Anti-Reflective Ultra Bright Screen. Customers can be confident that in any type of weather condition, day or night content will be visible. Temperature regulated case to ensure the screen does not over heat or will not freeze. With its sleek design and color options of black, this kiosk is a standout in any location. BrightSign Built-In Media Player included.

LCD Panel Type	46.96 Inches IPS LCD	
Native Resolution	1920x1080	
Backlight	LED	
Brightness	3000 nit	
Default Color Temperature	D65 (6500K)	
Contrast Ratio	1,300:1 (static), 1,000,000:1 (dyn)	
Color Depth	10 bits	
Response Time	12 ms (typ)	
Viewing Angle	178°/178°	
Light Life Time	50,000 hrs (typ)	
Blackening Defect Free	Up to 230°F	
Panel Surface	AG Haze 10%, 3H	
Operating Temperature	-40°F - 122°F	
Storage Temperature	-40°F - 140°F	
Humidity	10% ~ 80% RH Non-condensing	
Power Supply	Internal	
Rated Voltage	100v	
Power On Mode	280W (typ), 390W (maz)	
Power Saving Mode	<1W	
AC Out	<100W	
Ports	DVI-D, RS-232, RJ-45	
Certification	CE/FCC/ROHS	

ccessories	Remote Control, Users Guide/Driver CD-ROM, Video Cable, Power Cable, RJ-45 Cable	
Nechanical	Bezel Width .4"/.4"/.4"/.4"	
Specs	Cabinet Color	Black
	Monitor Dimension (LxHxD, w/o stand)	42.09x24.13x3.54"
	Monitor Weight	70.55 lbs/79.37 lbs
	VESA Mounting (dimension)	15.75x15.75″
User Interface	Language	English
	Daisy Chain	DVI, RS-232
	Proof of Image Retention	Yes
	Dimming Control (DCR)	Yes
	Built-In Video Wall Support	Up to 15x15
	ID Setting for Daisy Chain	Yes
	On/Off Scheduling	Yes
	Ambient Light Sensor	Yes
	Total Turn-On Time	Yes
	Internal Temperature Sensor	Yes
	Network Control	RS-232, RJ45
	OSD Menu Rotation	Yes
(insk	Overall	31″w x 72″ h
Dimensions	Top Depth With Vent	9″
	Base Depth	7.1″
	Back Doors Overall	76.6″ x 30″
	Top Door	35.5″
	Bottom Door	35.5″
		1