



UV550PDBLK  
Black



### Outdoor Skirted Kiosk

Anti-Reflective Ultra Bright Screen. Customers can be confident that in any type of weather condition, day or night content will be visible. Temperature regulated case to ensure the screen does not over heat or will not freeze. With its sleek design and color options of black, this kiosk is a standout in any location. BrightSign Built-In Media Player

LCD Panel Type	54.64 Inches IPS LCD
Native Resolution	1920x1080
Backlight	LED
Brightness	3500 nit
Default Color Temperature	D65 (6500K)
Contrast Ratio	3,000:1 (static), 1,000,000:1 (dyn)
Color Depth	8 bits
Response Time	9ms (typ)
Viewing Angle	178°/178°
Light Life Time	100,000 hrs (typ)
Blackening Defect Free	Up to 230°F
Panel Surface	AR 1.5%, 2H
Operating Temperature	-40°F - 122°F
Storage Temperature	-40°F - 140°F
Humidity	10% ~ 80% RH Non-condensing
Power Supply	Internal
Rated Voltage	100v
Power On Mode	280W (typ), 390W (maz)
Power Saving Mode	<1W
AC Out	<100W
Certification	CE/FCC/ROHS
Ports	DVI-D, DisplayPort, RS-232, RJ-45, Audio

Accessories	(Included) Pwer Cord, DVI Cable, RJ45 Cable, RS232 Cable, Remote Controller, Batteries, QSG. (Optional) AD Box, Extension Sensor Kit	
Mechanical Specs	Bezel Width	.43"/.43"/.43"/.43"
	Cabinet Color	Black
	Monitor Dimension (LxHxD, w/o stand)	48.82x27.95x3.45"
	Monitor Weight	60.67 lbs/71.65 lbs
	VESA Mounting (dimension)	15.75x15.75"
	Fanless Design	Yes
User Interface	Orientation	Portrait
	Daisy Chain	DVI, RS-232
	Language	English
	Proof of Image Retention	Yes
	Dimming Control (DCR)	Yes
	Built-In Video Wall Support	Up to 6x6
	ID Setting for Daisy Chain	Yes
	On/Off Scheduling	Yes
	Ambient Light Sensor	Yes
	Total Turn-On Time	Yes
	Internal Temperature Sensor	Yes
	Network Control	RS-232, RJ45
	OSD Menu Rotation	Yes
Carrying Handles	Yes	
Kiosk Dimensions	Overall	31"w x 77.7" h
	Top Depth With Vent	9"
	Base Depth	7.1"
	Back Doors Overall	76.6" x 30"
	Top Door	38.3" x 30"
Bottom Door	38.3" x 30"	