



55" Video Wall Display

This product features ultra narrow bezel, LG commercial grade IPS panel and patented tile technology. It supports USB port and internet content publishing. Smart functions include scheduled power on/off, intelligent temperature control, brightness adjustment and etc.



Easy Setup with RS232 In And Out

Each video wall display features and RS232 in and out connection. RS232 is a standard of serial communication between a PC and multiple displays, and makes video wall configuration a breeze.



Full HD 1080p with HDMI

- Scale up or scale down. Endless possibilities with a multiple display control.
- Automatic power on/off function allows you to schedule when the display will turn on or off. Schedule by time of day or calendar date.
- Abundant I/O ports: Video, Audio, VGA, DVI, RGB/HV, YPbPr, HDMI, USB, RS232, RJ45

| | |
|-----------------------|--|
| Model | PD55NL |
| Display Screen Size | 54.64" |
| Resolution | 1920 x 1080 |
| Product Size (inches) | 47.77"[H] x 26.94"[W] x 4.64"[D] |
| Display Size (inches) | 47.63"[H] x 26.80"[W] |
| Net Weight | 70.55 lbs. |
| Brightness | 450 cd/m ² |
| Aspect Ratio | 16:9 |
| Contrast Ratio | 1300:1 (Typ.) |
| Input Power Voltage | AC 100-240 V (50Hz-60Hz) |
| Working Temperature | 32° to 122° F |
| Colors | 10Bit[D], 1.06 Billion |
| Video Format | avi, mp4, ts, trp, mkv, mov, mpg, dat, vob |
| Audio Format | mp3, wma, m4a, aac |
| Picture and Text | bmp, jpg, jpeg, png, txt |
| Content Input Method | USB, LAN, WAN |
| Ports | Video, VGA, DBI, REG/HV, HDMI, YPbPr, Audio, RS232, RJ45 |
| Power Consumption | 165W |
| Viewing Angle | 178° |
| Time Control | Supports multi on and off task, automatically switch channel |
| Accessories | Manual, Guarantee Card, Remote Control, Power Cable, VGA Cable, RS232 Cable, RJ45 Cable, DID Silica Gel Gasket |
| VESA Pattern | 300 x 600mm |