## 55" High Bright Window Display

**DIGITAL COMPLETE**

55" High Bright Window Display with Brightsign, NoviSign, Windows, or Android built-in. COMPLETE kiosk, media and content solution.

### 55" HD Commercial Display
Specially designed for commercial market, this product features your choice of Built-In Media Player*, ideal for retail, hospitals, public spaces, government, and more.

### Industrial Ultra Slim Design
A sleek, stylish design that offers the ruggedness needed in today's market place and the simple installation and maintenance design wanted by today's technicians.

### High Bright Screens
Designed to display in windows without a distracting glare.

## Specifications

| | |
|---|---|
| LCD Panel Type | 54.64" |
| Resolution | 1920 x 1080p |
| Brightness | 3500 nits |
| Contrast Ratio | 3000:1 |
| Viewing Angle | 178° |
| Light Life Timer | 100,000 hrs. |
| Ambient Light Sensor | Yes |
| On/Off Scheduling | Yes |
| Rated Voltage | 100v - 240v / 50Hz - 60Hz |
| Power Supply | Internal |
| Power On Mode | 160w (typ.) - 240w (max) |
| Display Size (inches) | 49" (W) x 28" (H) x 3" (D) |
| Bezel Width (T/B/L/R) | Even 10.9mm |
| Display Weight | 61 lbs. |
| Gross Weight | 72 lbs. |
| VESA Mounting Dimension | 400mm x 400mm |
| HDMI | In x1 |
| DisplayPort | In x1 |
| DVI-D | In x1, Out x1 |
| RS-232 | In x1, Out x1 |
| RJ-45 | In x1 |
| USB | x1 |
| SD Slot | x1 |
| Audio Port | Out x1 |
| Working Temperature | 32° to 113° F |
| Accessories | Quickstart Guide, Power Cord, Remote Control (with batteries), Extension Sensor Kit 302 (optional), Thermal Sensor Kit 201 (optional) |