55-inch Infrared Touch Portrait Digital Signage







55" HD Commercial Display w/ BrightSign

Specially designed for commercial market, this product features BrightSign Built-In, LG IPS high luminance panel and professional DCPI color adjustment technology. It support our CDMS software, online publish/manage contents is quite easy.



BrightAuthor Software

BrightAuthor is a PC software application for BrightSign that makes creating, publishing and managing interactive Bright-Sign presentations simple and dependable.



Industrial Ultra Slim Design

A sleek, stylish yet rugged design, with simple installation and maintenance, offers a perfect all-in-one solution for today's marketplace.



IP Streaming

HD Video IP streaming is available on all BrightSign built-in displays. Buffer media streams for smooth playback. Play streaming media in HTML5 assets or in BrightAuthor's video, audio or MJPEG stream states.



UDP Controls

Supported via the Ethernet port for video wall synchronization, mobile device interactivity, and messaging between BrightSign and third-party devices such as projectors, lighting, etc. and can be integrated with other show controllers.

Panel		55" inches LED backlit
Aspect Ratio		9:16
Resolution		1920×1080
Brightness		400 cd/m2
Contrast Ratio		5000:1
Viewing Angle		178°
Display Colors		16.7M
Life Expectance		60000 hours
Ports		(1) RJ45, (2) USB, (1) HDMI, (1) VGA,
		(1) Audio, TF socket, SIM card socket
Input Power Voltage		AC 110-240V (50Hz-60Hz)
Power Consumption		80W
Working Temperature		32° - 104°
Product Size		72.65" H x 32.55" W x 3.13" D
Net Weight		195LBS
Speaker		6W 8Ω
Supported Media	Video Format	AVI, MP4, TS, TRP, MKV, MOV, MPG, DAT, VOB
	Audio Format	MP3, WMA, M4A, AAC
	Picture And	BMP, JPG, JPEG, PNG, TXT
	Text	
	Screen Mode	Landscape, portrait, full screen,
	Play time	divided screen Support
	control	Зиррин
	Content Input Method	SD Card, LAN
A .	метпоа	
Accessories		Remote Control, AC Power Cord, Key
WIFI PECET via watchdoa		YES (Optional)
RESET via watchdog Time Control		Support multi on and off task,
		automatically switch channel

UVP-FLY-234-REV 0