



55" Freestanding Commercial Kiosk

Introducing the highly acclaimed 55-inch Freestanding Commercial Kiosk, the leading LCD digital display solution for retail businesses. Renowned for its popularity and versatility, this kiosk has become a favored choice among retailers aiming to make a significant impact on their customers. With its sleek design and impressive display capabilities, this kiosk captures attention and provides an engaging platform for showcasing promotional content, advertisements, and product information.

Designed with convenience in mind, the freestanding commercial kiosk features casters on the base of the unit, enabling effortless mobility and placement in any desired location. Whether you want to attract attention near the entrance, highlight specific product displays, or adapt to different store layouts, the casters ensure easy movement of the kiosk. This flexibility allows you to optimize customer engagement by strategically positioning the kiosk for maximum impact, creating an immersive and captivating retail experience that leaves a lasting impression.

The 55-inch Freestanding Commercial Kiosk is the ultimate display solution for retailers seeking a powerful tool to engage customers and drive sales. With its versatile size, convenient mobility, and exceptional visual capabilities, this kiosk offers a dynamic platform for delivering impactful content and captivating the attention of shoppers. Experience the effectiveness of this popular LCD digital display and elevate your retail business to new heights.

Specifications

Panel	LCD Size	55"
	Light Source	LED backlight
	Resolution	1920 x 1080 pixels
	Brightness	500cd/m ²
	Contrast	1200:1
	Response	10ms
	Pixel pitch	0.63(H) x 0.63(V) mm
	Refresh rate	60Hz
	Viewing angle	178°(H) x 178°(V)
	Color saturation	72%
	Viewable area	1209.6 (H) x 680.4 (V) mm
	Chromaticness	16.7 M
	Power Supply	Voltage
Power Consumption		≤120W
Environment	Operating temperature	0~40°C
	Storage temperature	-10~60°C
	Operating humidity	20~80% RH Non-condensing
	Storage humidity	10~60% RH Non-condensing
	Maximum operating	18 hours/day

I/O interfaces	TF	N/A
	Ethernet (RJ45)	1
	HDMI	N/A
	VGA	N/A
	3.5mm headphone	N/A
	USB	2
	WiFi	1
	Type-C OTG	N/A
	SIM	N/A
Structure	Net weight	No touch: 66kgs IR Touch: 69kgs
	Gross weight	No touch: 85kgs IR Touch: 88kgs
	Unit dims. (WxDxH)	No touch: 810 x 50 x 1980mm IR Touch: 810 x 70 x 1980mm
	Package dims. (WxDxH)	No touch: 2040 x 215 x 950mm IR Touch: 2040 x 240 x 950mm
	Shell material	Aluminum profile/sheet metal
	Shell color	Black/white