

## **65" Freestanding Non-Touch Kiosk**

Introducing the highly sought-after 65-inch Freestanding Non-Touch Kiosk, the go-to LCD digital display solution for retail businesses. Renowned for its popularity and versatility, this kiosk has become a staple choice for retailers looking to make a lasting impact on their customers. With its impressive size and vibrant display, this kiosk commands attention and provides an engaging platform for showcasing promotional content, advertisements, and product information.

Designed with convenience in mind, this freestanding kiosk features casters on the base of the unit, allowing for easy mobility and placement in any desired location. Whether you want to attract attention near the entrance, highlight specific product displays, or cater to different store layouts, the casters enable effortless movement of the kiosk. This flexibility ensures that you can optimize customer engagement by strategically positioning the kiosk for maximum impact, creating a captivating and immersive retail experience that leaves a lasting impression.

The 65-inch Freestanding Non-Touch Kiosk is the perfect display solution for retailers seeking a powerful tool to engage customers and drive sales. With its impressive size, easy maneuverability, and stunning visual capabilities, this kiosk offers a dynamic platform for delivering impactful content and capturing the attention of shoppers. Experience the power of this popular LCD digital display, and elevate your retail business to new heights.

## **Specifications**

Light Source         LED backlight           Resolution         3840 x 2160 pixels           Brightness         500cd/m²           Contrast         1200:1           Response         10ms           Pixel pitch         0.37(H) x 0.37(V) mm           Refresh rate         60Hz           Viewing angle         178°(H) x 178°(V)	Panel	LCD Size	65"
Brightness   500cd/m²		Light Source	LED backlight
Contrast   1200:1     Response   10ms     Pixel pitch   0.37(H) x 0.37(V) mm     Refresh rate   60Hz     Viewing angle   178°(H) x 178°(V)		Resolution	3840 x 2160 pixels
Panel         Response         10ms           Pixel pitch         0.37(H) x 0.37(V) mm           Refresh rate         60Hz           Viewing angle         178°(H) x 178°(V)		Brightness	500cd/m <sup>2</sup>
Panel Pixel pitch  Pixel pitch  0.37(H) x 0.37(V) mm  Refresh rate  60Hz  Viewing angle  178°(H) x 178°(V)		Contrast	1200:1
Refresh rate         60Hz           Viewing angle         178°(H) x 178°(V)		Response	10ms
Viewing angle 178°(H) x 178°(V)		Pixel pitch	0.37(H) x 0.37(V) mm
		Refresh rate	60Hz
		Viewing angle	178°(H) x 178°(V)
Color saturation 72%		Color saturation	72%
Viewable area 1428.5 (H) x 803.5 (V) mm		Viewable area	1428.5 (H) x 803.5 (V) mm
Chromaticness 1.07 Billion		Chromaticness	1.07 Billion
Power Voltage 100V ~ 240V, 50-60Hz	Power	Voltage	100V ~ 240V, 50-60Hz
Supply Power Consumption ≤310W	Supply	Power Consumption	≤310W
Operating temperature 0~40°C		Operating temperature	0~40°C
Storage temperature -10~60°C		Storage temperature	-10~60°C
Environment Operating humidity 20~80% RH Non-condensing	Environment	Operating humidity	20~80% RH Non-condensing
Storage humidity 10~60% RH Non-condensing		Storage humidity	10~60% RH Non-condensing
Maximum operating 18 hours/day		Maximum operating	18 hours/day

	TF	N/A
I/O interfaces	Ethernet (RJ45)	1
	HDMI	N/A
	VGA	N/A
	3.5mm headphone	N/A
	USB	2
	WiFi	1
	Type-C OTG	N/A
	SIM	N/A
Structure	Net weight	No touch: 87kgs
	Gross weight	No touch: 105kgs
	Unit dims. (WxDxH)	No touch: 950 x 110 x 1690mm
	Package dims. (WxDxH)	No touch: 1790 x 270 x 1050mm
	Shell material	Aluminum profile/sheet metal
	Shell color	Black/white