



### 40" Commercial Grade Display

Our commercial grade displays make it easy to display the content that you want. These monitors can be used as a single monitor, or can be tiled as a monitor wall, and our professional displays offer continuous, reliable operation 24 hours a day, 7 days a week. With so many configuration options, the possibilities are endless!

## 16:9 Aspect Ratio

The M40S1 offers a 16:9 Aspect Ratio, for more configuration options.

#### **Quality Displays**

These displays last longer, and conserve more energy than traditional displays.

## Easy Setup with RS232 In And Out

Each display features an RS232 in and out connection. RS232 is a standard of serial communication between a PC and multiple displays, and makes monitor wall configuration a breeze.

# With the Addition of a Mini-PC you Can Control Your Content From Anywhere

With the addition of a mini-PC you can control your content from anywhere when equipped with a mini-PC, you can control your content using an RJ45 (Ethernet) cable or over WIFI. This means that you can change your content of long distances without using expensive cables.

Model	M40S1
Display Screen Size	40"
Product Size	37.64" (W) x 21.85" (H) x 3.69" (D)
Display Size	34.93" (W) x 19.67" (H)
Net Weight	51 lbs
Gross Weight	63 lbs
Pixel Pitch	0.461(H)x0.461(V)
Resolution	1920x1080
Brightness	500 cd/m2
Contrast Ratio	5000:1 typ
Viewing Angle	178°
Aspect Ratio	16:9
Colors	16.7M
Response Time	8ms
Color Temperature	10000K
Life Time	50000 hours
Power Consumption	240W
Input Port	Video, VGA, DVI, RGB/HV, YPbPr, HDMI
Outout Port	Video, Audio
Control Port	RS232 IN DB9(female) RS232 OUT DB9(male)
Built In Tiling Software	Yes
Accessories	Remote control, AC Power Cord, VGA cable